

Appln. No. 10/077,215

Attorney Docket No. 10541-1273

**I. Listing of Claims**

1. (Cancelled)

2. (Cancelled)

3. (Currently amended): The [[invention of claim 1]] shaft of claim 6, wherein said coating is nylon.

4. (Currently amended): The [[invention of claim 1]] shaft of claim 6, wherein said coating is tungsten disulfide.

5. (Currently amended): The [[invention]] shaft of claim 4, wherein said coating measures less than approximately 10 microns thick.

6.. (Currently amended): [[The invention of claim 1]] A shaft to transfer torque in a vehicle, comprising:

a first member having internal splines; and

a second member having external splines engagable with said internal splines to allow telescopic movement between said first member and said second member and to transfer torque between said first member and said second member,

wherein said external [[spline]] splines further [[includes]] include an isotropic surface finish, and

wherein said external splines have a coating applied to the isotropic surface finish to reduce friction during the telescopic movement.

-2-

BRINKS  
HOFER  
GILSON  
& LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60611-5599

Appln. No. 10/077,215

Attorney Docket No. 10541-1273

7. (Cancelled)

8. (Cancelled)

9. (Currently amended): The [[invention of claim 7]] shaft of claim 12, wherein said coating is nylon.

10. (Currently amended): The [[invention of claim 7]] suspension system of claim 12, wherein said coating is tungsten disulfide.

11. (Currently amended): The [[invention]] suspension system of claim 10, wherein said coating measures less than approximately 10 microns thick.

12. (Currently amended): [[The invention of claim 7]] A suspension system for a vehicle having a wheel and a power distribution device, the suspension system comprising:

a biasing device to support the vehicle on the wheel and to absorb road imperfections; and

a shaft to transfer torque from the power distribution device to said wheel, the shaft including a first member having internal splines and a second member having external splines engagable with said internal splines to allow telescopic movement between said first member and said second member and to transfer torque between said first member and said second member;

wherein said external [[spline]] splines further [[includes]] include an isotropic surface finish, and

wherein said external splines have a coating applied to the isotropic surface finish to reduce friction during the telescopic movement.

13. (Currently amended): The [[invention of claim 7]] suspension system of claim 12, wherein one of said first and second members is adapted to couple with the power distribution device and one of said first and second members is adapted to couple with the wheel.

-3-

BRINKS  
HOFER  
GILSON  
& LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60611-5599

Appln. No. 10/077,215

Attorney Docket No. 10541-1273

14. (Currently amended): The [[invention of claim 7]] suspension system of claim 12, further comprising a first universal joint coupling said shaft and the power distribution device.

15. (Currently amended): The [[invention]] suspension system of claim 14, further comprising a second universal joint coupling said shaft and the wheel.

---

-4-

BRINKS
HOFER
GILSON
& LIONE

BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60611-5599